

# CLD downlight

## 90mm



### SPECIFICATIONS

#### Material Specifications

<b>Material Specifications</b>	PC Housing / Aluminium Diecast LED Module
<b>Colour</b>	Matt White / Matt Black
<b>Cutout</b>	90mm
<b>Dimensions</b>	98mm (Face Dia) x 123mm (H)
<b>Ingress Protection</b>	IP44
<b>Warranty</b>	5 Year Replacement

#### Electrical Specifications

<b>LED Wattage</b>	15W
<b>Power Supply</b>	Tridonic TRIAC
<b>Options</b>	Tridonic DALI
<b>Operating Temperature (Ta)</b>	-20°C to +40°C
<b>Connection Method</b>	Australian Flex & Plug

#### Optic Specifications

<b>Light Source</b>	Citizen COB
<b>CRI</b>	90+
<b>Delivered Lumens</b>	1200Lm
<b>Beam Angle</b>	60° (Available in 28° & 38° Options)
<b>Correlated Colour Temperature</b>	2700K / 3000K / 4000K / 5000K
<b>Material Specifications</b>	<2
<b>Rated Lifetime (L80B10)</b>	>90,000Hr

### VARIATIONS

<b>CLD3790-27K-W</b>	15W, Matt White, 60°, TRIAC, 2700K
<b>CLD3790-3K-W</b>	15W, Matt White, 60°, TRIAC, 3000K
<b>CLD3790-4K-W</b>	15W, Matt White, 60°, TRIAC, 4000K
<b>CLD3790-5K-W</b>	15W, Matt White, 60°, TRIAC, 5000K
<b>CLD3790-27K-B</b>	15W, Matt Black, 60°, TRIAC, 2700K
<b>CLD3790-3K-B</b>	15W, Matt Black, 60°, TRIAC, 3000K
<b>CLD3790-4K-B</b>	15W, Matt Black, 60°, TRIAC, 4000K
<b>CLD3790-4K-B</b>	15W, Matt Black, 60°, TRIAC, 5000K

