

CLDS - DOWNLIGHT

75mm



IP44

SPECIFICATIONS

Material Specifications

| | |
|---------------------------|--|
| Material | PC Housing / Aluminium Die-cast LED Module |
| Colour | Matt White / Matt Black |
| Cutout | 75mm |
| Dimensions | 82mm (Face Dia) x 103mm (H) |
| Ingress Protection | IP44 |
| Warranty | 5 Year Replacement |

Electrical Specifications

| | |
|-----------------------------------|------------------------|
| LED Wattage | 15W |
| Power Supply | Tridonic TRIAC |
| Options | Tridonic DALI |
| Operating Temperature (Ta) | -20°C to +40°C |
| Connection Method | Australian Flex & Plug |

Optic Specifications

| | |
|--------------------------------------|--------------------------------------|
| Light Source | Citizen COB |
| CRI | 90+ |
| Delivered Lumens | 1200Lm |
| Beam Angle | 55° (Available in 28° & 38° Options) |
| Correlated Colour Temperature | 2700K / 3000K / 4000K / 5000K |
| Colour Deviation | <2 |
| Rated Lifetime (L80B10) | >90,000hr |

VARIATIONS

| | |
|-----------------------|------------------------------------|
| CLDS3775-27K-W | 15W, Matt White, 55°, TRIAC, 2700K |
| CLDS3775-3K-W | 15W, Matt White, 55°, TRIAC, 3000K |
| CLDS3775-4K-W | 15W, Matt White, 55°, TRIAC, 4000K |
| CLDS3775-5K-W | 15W, Matt White, 55°, TRIAC, 5000K |
| CLDS3775-27-B | 15W, Matt Black, 55°, TRIAC, 2700K |
| CLDS3775-30-B | 15W, Matt Black, 55°, TRIAC, 3000K |
| CLDS3775-40-B | 15W, Matt Black, 55°, TRIAC, 4000K |
| CLDS3775-50-B | 15W, Matt Black, 55°, TRIAC, 5000K |

