

DL03-6 IP65 Downlight

160mm



IP65

SPECIFICATIONS

Material Specifications



Material Specifications	Aluminium Diecast Housing / Clear Diffuser (Satin & Opal Lens Options Available)
Colour	White Trim (Custom Colour Options Available)
Cutout	160mm
Dimensions	183mm (Face Dia) x 80mm (H)
Ingress Protection	IP65
Warranty	5 Year Replacement

Electrical Specifications

LED Wattage	40W Max.
Power Supply	Tridonic Fixed Output (NFC Programmable)
Options	Tridonic DALI
Operating Temperature (Ta)	-20°C to +45°C
Connection Method	Australian Flex & Plug

Optic Specifications

Light Source	Philips COB
CRI	90+
Delivered Lumens	680Lm - 3400Lm
Beam Angle	60°
Correlated Colour Temperature	2700K / 3000K / 3500K / 4000K / 5000K
Rated Lifetime (L80B10)	>50,000hr



VARIATIONS

DL03-6-27K	8W - 40W Multi-Watt, 2700K
DL03-6-3K	8W - 40W Multi-Watt, 3000K
DL03-6-35K	8W - 40W Multi-Watt, 3500K
DL03-6-4K	8W - 40W Multi-Watt, 4000K
DL03-6-5K	8W - 40W Multi-Watt, 5000K