

DL03-8 IP65 Downlight

200mm



IP65

SPECIFICATIONS

Material Specifications

Material Specifications	Aluminium Die-cast Housing / Clear Diffuser (Satin & Opal Lens Options Available)
Colour	White Trim (Custom Colour Options Available)
Dimensions	226mm (Face Dia) x 96mm (H)
Cutout	200mm
Ingress Protection	IP65
Warranty	5 Year Replacement

Electrical Specifications

LED Wattage	50W
Power Supply	Tridonic Fixed Output (NFC Programmable)
Options	Tridonic DALI
Operating Temperature (Ta)	-20°C to +40°C
Connection Method	Australian Flex & Plug

Optic Specifications

Light Source	CITIZEN COB
CRI	90+
Delivered Lumens	680Lm - 4250Lm
Beam Angle	60°
Correlated Colour Temperature	2700K / 3000K / 3500K / 4000K / 5000K
Rated Lifetime (L80B10)	>50,000hr

VARIATIONS

DL03-8-27K	8W - 50W Multi-Watt, 2700K
DL03-8-3K	8W - 50W Multi-Watt, 3000K
DL03-8-35K	8W - 50W Multi-Watt, 3500K
DL03-8-4K	8W - 50W Multi-Watt, 4000K
DL03-8-5K	8W - 50W Multi-Watt, 5000K

