

Exterior / Wall Pack

IP66 - IK10

Designed & Engineered for Harsh External Applications.



SPECIFICATIONS

Material Specifications

Material	Die-cast Aluminium Housing
Finish	Textured Powder Coat (Black or White)
Dimensions	190mm(H) x 325(W) x 160mm(D)
Mounting	Wall Mtd
Ingress Protection	IP66
Impact Rating	IK10
Warranty	5 Year Replacement

Electrical Specifications

Power Supply	240V 50Hz
Operating Temperature (Ta)	-40°C to +50°C

Optic Specifications

Light Source	LED
Delivered Lumens	.
CRI	70+
Correlated Colour Temperature	3000K / 4000K / 5000K
Reported L70 (Hours)	> 60,000 Hrs

VARIATIONS

GDA-30-T2-3K-W	30W Wide, White, 3000K
GDA-30-T3-3K-W	30W Medium, White, 3000K
GDA-30-T4-3K-W	30W Forward, White, 3000K
GDA-30-T2-4K-W	30W Wide, White, 4000K
GDA-30-T3-4K-W	30W Medium, White, 4000K
GDA-30-T4-4K-W	30W Forward, White, 4000K
GDA-30-T2-5K-W	30W Wide, White, 5000K
GDA-30-T3-5K-W	30W Medium, White, 5000K
GDA-30-T4-5K-W	30W Forward, White, 5000K
GDA-30-T2-3K-B	30W Wide, Black, 3000K
GDA-30-T3-3K-B	30W Medium, Black, 3000K
GDA-30-T4-3K-B	30W Forward, Black, 3000K
GDA-30-T2-4K-B	30W Wide, Black, 4000K
GDA-30-T3-4K-B	30W Medium, Black, 4000K
GDA-30-T4-4K-B	30W Forward, Black, 4000K
GDA-30-T2-5K-B	30W Wide, Black, 5000K
GDA-30-T3-5K-B	30W Medium, Black, 5000K
GDA-30-T4-5K-B	30W Forward, Black, 5000K

