

# DALI DIMMABLE CONSTANT VOLTAGE IP20



## SPECIFICATIONS

### Material Specifications

|                    |                       |
|--------------------|-----------------------|
| Material           | Polycarbonate UL44-VO |
| Ingress Protection | IP20                  |
| Warranty           | 5 Year Replacement    |

### Electrical Specifications

|                   |                               |
|-------------------|-------------------------------|
| Input Type        | 180-240V, 50-60Hz             |
| Connection Method | Australian F&P                |
| Output Voltage    | 12V - 24V DC Constant Voltage |
| Dimming           | DALI                          |
| Power Factor      | >0.95 @ Full Load             |
| Thermal Testing   | Ta Rating -30°C to +40°C      |
| Dimming           | 5% - 100% Dimming Range       |

## VARIATIONS

|              |                                |
|--------------|--------------------------------|
| HDL-CV-12-12 | 12W, 12V - 94mm x 36mm x 17mm  |
| HDL-CV-12-24 | 12W, 24V - 94mm x 36mm x 17mm  |
| HDL-CV-20-12 | 20W, 12V - 94mm x 36mm x 17mm  |
| HDL-CV-20-24 | 20W, 24V - 94mm x 36mm x 17mm  |
| HDL-CV-30-12 | 30W, 12V - 107mm x 40mm x 22mm |
| HDL-CV-30-24 | 30W, 24V - 107mm x 40mm x 22mm |
| HDL-CV-40-12 | 40W, 12V - 132mm x 44mm x 28mm |
| HDL-CV-40-24 | 40W, 24V - 132mm x 44mm x 28mm |
| HDL-CV-60-12 | 60W, 12V - 132mm x 44mm x 28mm |
| HDL-CV-60-24 | 60W, 24V - 132mm x 44mm x 28mm |
| HDL-CV-80-12 | 80W, 12V -170mm x 50mm x 30mm  |
| HDL-CV-80-24 | 80W, 24V -170mm x 50mm x 30mm  |

