

# Adjustable Beam Tracklight

## Large



### SPECIFICATIONS

#### Material Specifications

|                    |                            |
|--------------------|----------------------------|
| Material           | Aluminium                  |
| Colour             | Matt White / Matt Black    |
| Dimensions         | 74mmmm (Dia) x 212.5mm (L) |
| Ingress Protection | IP20                       |
| Warranty           | 5 Year Replacement         |

#### Electrical Specifications

|                            |                                            |
|----------------------------|--------------------------------------------|
| LED Wattage                | 35W                                        |
| Power Supply               | TRIAC Dimmable                             |
| Options                    | DALI                                       |
| Operating Temperature (Ta) | -5°C to +35°C                              |
| Connection Method          | 3~ Track Adaptor (1~ Available on request) |

#### Optic Specifications

|                               |                       |
|-------------------------------|-----------------------|
| Light Source                  | Luminus CXM-14 Gen 3  |
| CRI                           | 90+                   |
| Delivered Lumens              | 1981Lm - 2312Lm       |
| Beam Angle                    | 12° - 50° Adjustable  |
| Correlated Colour Temperature | 2700K / 3000K / 4000K |
| Rated Lifetime (L70B20)       | >50,000hr             |

### VARIATIONS

|               |                                     |
|---------------|-------------------------------------|
| L4T527-27K-WH | 35W, White, 12° - 50°, Triac, 2700K |
| L4T527-3K-WH  | 35W, White, 12° - 50°, Triac, 3000K |
| L4T527-4K-WH  | 35W, White, 12° - 50°, Triac, 4000K |
| L4T527-27K-BL | 35W, Black, 12° - 50°, Triac, 2700K |
| L4T527-3K-BL  | 35W, Black, 12° - 50°, Triac, 3000K |
| L4T527-4K-BL  | 35W, Black, 12° - 50°, Triac, 4000K |

